

JTM-1050EVS2/230 MILL WITH 2-AXIS ACU-RITE MILLPWR G2 CNC CONTROLLER AND AIR POWERED DRAW BAR

690685

JET offers complete, factory-installed CNC packages with your choice of 2 or 3-axis CNC controls. The Computer Numerical Control system brings the added precision of digital automation to the process, allowing the user greater control and efficiency. Meehanite® casted JET Vertical Mills with CNC packages deliver accurate results every time. All the features you've come to expect backed by the industry-leading JET Two Year Warranty



FEATURES

- CNC Electronic Variable Speed Vertical Milling Machine Package JTM-1050EVS
- Features of the ACU-RITE MILLPWR G2 CNC Package
- Precision Ground Ball Screws eliminate backlash for precise lateral movements
- Closed loop feedback using Acu-Rite precision linear encoders with 0.00005" resolution
- Powerful DC Servo motor assemblies that include mounting castings and hardware
- Handwheels are included for manual operation
- Features of the ACU-RITE MILLPWR G2 CONTROLLER
- USB + Ethernet compatible
- Simplified navigation that eliminates multiple menu screens
- 12.1" High resolution display (1024 x 768) with 3D graphics
- 1 GHz Celeron® M processor
- Expanded tool library and Datum offsets
- Program preview provides a graphical representation prior to operation
- Program size limit increased by 90% to 9,999 steps
- Jog Control allows table movement, quickly from one location to another - using one axis at a time or any two axes simultaneously
- 3-D Contouring, ability to import and run G-code files from CAD/CAM programs
- Mirror/Repeat/Rotate/Explode/Merge, easily manipulate, explode and merge part programs to save time and reduce program steps

RESOURCES

- [View More Details](#)

SPECIFICATIONS

CNC Package	ACU-RITE MILLPWR® G2
Number of Axis	2
Table Size (L x W) (In.)	10 x 50
Power Draw Bar	Pneumatic
Spindle Taper (In. x TPI)	R-8
Quill Diameter (In.)	3-3/8
Number of Spindle Speeds	Variable
Range of Spindle Speeds (RPM)	60 - 4,500
Quill Down Feed Rates (IPR)	.0015 - .003 - .006
Spindle Travel (In.)	5
Head Movement (Deg.)	90° R & L, 45° F & B
Max Distance Spindle to Table (In.)	20-3/4
Distance Spindle to Column (Max.) (In.)	26-3/4
Distance Spindle to Column (Min.) (In.)	4-3/4
Collet Capacity	1/8 - 7/8
Table Longitudinal Travel (In.)	35-1/3
Table Longitudinal Travel With Powerfeed (In.)	29-7/8

STAND BEHIND YOUR WORK™



550+ SERVICE CENTERS NATIONWIDE

INDUSTRY-LEADING WARRANTIES

EXPERT TECHNICAL SERVICE